



FILTRATION GROUP FIBERGLASS RIGID PAC

- High lofted ultra fine fiberglass media
- Rigid format prevents unloading in variable air volume systems
- Used in both side access & built-up filter banks
- Replaces traditional pocket-style filters
- Galvanized steel frame provides rigid construction
- Available in box-style or single header
- UL900 Class 2



DESCRIPTION

The Fiberglass Rigid Pac is an extended surface, medium to high efficiency filter. Its lofted ultra fine fiberglass media provides excellent dust holding capacity and coupled with its rigid construction virtually eliminates dust particle unloading downstream of the filter.

A galvanized steel frame, diagonal support bracing, moisture resistant media contour stabilizers and metal media support grid enhance the durability of this filter. This durability eliminates media oscillation and media pull-away. The media of this filter is adhesively bonded to all four sides of the frame to eliminate air bypass. The Aerostar RF is available in ASHRAE 40-45%, 60-65%, 80-85% and 90-95% efficiencies.

BENEFITS

The Aerostar RF is the ideal solution to IAQ problems that demand a high efficiency, long lasting rigid filter without costly modification to existing equipment. The secure, superior performance of this filter helps reduce costly maintenance.

The Rigid Pac can withstand many unfavorable conditions, especially variable air volume (VAV) without negatively effecting the performance of the filter.

APPLICATIONS

The Aerostar RF can be used in place of many high efficiency style filters. This filter may be used in spaces requiring 6" or 12' filters and is suitable for use in most commercial and industrial HVAC systems. This filter can upgrade your current system by providing exceptional filter integrity and consistent performance.

The Rigid Pac can be used as a pre-filter for higher efficiency products or a final filter in HVAC systems that require a high level of efficiency and cleanliness. It is designed for ease of installation in either side access systems or built-up banks. It is available in traditional box style or single header versions.

Distributed by:



FLORENCE FILTER CORPORATION

"30 Years of Filter Excellence"

www.florencefilter.com

530 W. Manville • Compton • California 90220
(310) 637-1137 • FAX (310) 631-4323 • (800) 776-2021

FIBERGLASS RIGID PAC
DIMENSIONS AND PERFORMANCE DATA
90-95% EFFICIENCY

BOX STYLE PART NO.*	SINGLE HEADER PART NO.*	NOMINAL FILTER SIZE	ACTUAL FILTER SIZE	RATED AIRFLOW CAPACITY (cfm)			INITIAL RESISTANCE ("W.G.)			MEDIA AREA (sq. ft.)
				LOW	MEDIUM	HIGH	LOW	MEDIUM	HIGH	
14946	16396	24x12x6	23 ³ / ₈ x11 ³ / ₈ x5 ¹ / ₂	300	450	600	.26	.40	.56	14
14947	16397	20x20x6	19 ³ / ₈ x19 ³ / ₈ x5 ¹ / ₂	450	650	850	.26	.40	.56	19
14948	16398	24x20x6	23 ³ / ₈ x19 ³ / ₈ x5 ¹ / ₂	500	750	1000	.26	.40	.56	24
14949	16399	24x24x6	23 ³ / ₈ x23 ³ / ₈ x5 ¹ / ₂	600	900	1200	.26	.40	.56	29
14950	16400	24x12x12	23 ³ / ₈ x11 ³ / ₈ x11 ¹ / ₂	500	750	1000	.26	.40	.68	28
14951	16401	20x20x12	19 ³ / ₈ x19 ³ / ₈ x11 ¹ / ₂	700	1050	1400	.26	.40	.68	39
14952	16402	24x20x12	23 ³ / ₈ x19 ³ / ₈ x11 ¹ / ₂	850	1250	1650	.26	.40	.68	47
14953	16403	24x24x12	23 ³ / ₈ x23 ³ / ₈ x11 ¹ / ₂	1000	1500	2000	.26	.40	.68	58

80-85% EFFICIENCY

BOX STYLE PART NO.*	SINGLE HEADER PART NO.*	NOMINAL FILTER SIZE	ACTUAL FILTER SIZE	RATED AIRFLOW CAPACITY (cfm)			INITIAL RESISTANCE ("W.G.)			MEDIA AREA (sq. ft.)
				LOW	MEDIUM	HIGH	LOW	MEDIUM	HIGH	
14954	16404	24x12x6	23 ³ / ₈ x11 ³ / ₈ x5 ¹ / ₂	300	450	600	.19	.28	.41	14
14955	16405	20x20x6	19 ³ / ₈ x19 ³ / ₈ x5 ¹ / ₂	450	650	850	.19	.28	.41	19
14956	16406	24x20x6	23 ³ / ₈ x19 ³ / ₈ x5 ¹ / ₂	500	750	1000	.19	.28	.41	24
14957	16407	24x24x6	23 ³ / ₈ x23 ³ / ₈ x5 ¹ / ₂	600	900	1200	.19	.28	.41	29
14958	16408	24x12x12	23 ³ / ₈ x11 ³ / ₈ x11 ¹ / ₂	500	750	1000	.19	.28	.50	28
14959	16409	20x20x12	19 ³ / ₈ x19 ³ / ₈ x11 ¹ / ₂	700	1050	1400	.19	.28	.50	39
14960	16410	24x20x12	23 ³ / ₈ x19 ³ / ₈ x11 ¹ / ₂	850	1250	1650	.19	.28	.50	47
14961	16411	24x24x12	23 ³ / ₈ x23 ³ / ₈ x11 ¹ / ₂	1000	1500	2000	.19	.28	.50	58

60-65% EFFICIENCY

BOX STYLE PART NO.*	SINGLE HEADER PART NO.*	NOMINAL FILTER SIZE	ACTUAL FILTER SIZE	RATED AIRFLOW CAPACITY (cfm)			INITIAL RESISTANCE ("W.G.)			MEDIA AREA (sq. ft.)
				LOW	MEDIUM	HIGH	LOW	MEDIUM	HIGH	
14962	16412	24x12x6	23 ³ / ₈ x11 ³ / ₈ x5 ¹ / ₂	400	600	750	.13	.26	.41	14
14963	16413	20x20x6	19 ³ / ₈ x19 ³ / ₈ x5 ¹ / ₂	550	800	1050	.13	.26	.41	19
14964	16414	24x20x6	23 ³ / ₈ x19 ³ / ₈ x5 ¹ / ₂	650	950	1250	.13	.26	.41	24
14965	16415	24x24x6	23 ³ / ₈ x23 ³ / ₈ x5 ¹ / ₂	750	1150	1500	.13	.26	.41	29
14966	16416	24x12x12	23 ³ / ₈ x11 ³ / ₈ x11 ¹ / ₂	500	750	1000	.14	.27	.42	28
14967	16417	20x20x12	19 ³ / ₈ x19 ³ / ₈ x11 ¹ / ₂	700	1050	1400	.14	.27	.42	39
14968	16418	24x20x12	23 ³ / ₈ x19 ³ / ₈ x11 ¹ / ₂	850	1250	1650	.14	.27	.42	47
14969	16419	24x24x12	23 ³ / ₈ x23 ³ / ₈ x11 ¹ / ₂	1000	1500	2000	.14	.27	.42	58

40-45% EFFICIENCY

BOX STYLE PART NO.*	SINGLE HEADER PART NO.*	NOMINAL FILTER SIZE	ACTUAL FILTER SIZE	RATED AIRFLOW CAPACITY (cfm)			INITIAL RESISTANCE ("W.G.)			MEDIA AREA (sq. ft.)
				LOW	MEDIUM	HIGH	LOW	MEDIUM	HIGH	
14970	16420	24x12x6	23 ³ / ₈ x11 ³ / ₈ x5 ¹ / ₂	500	750	1000	.21	.26	.30	14
14971	16421	20x20x6	19 ³ / ₈ x19 ³ / ₈ x5 ¹ / ₂	700	1050	1400	.21	.26	.30	19
14972	16422	24x20x6	23 ³ / ₈ x19 ³ / ₈ x5 ¹ / ₂	825	1200	1650	.21	.26	.30	24
14973	16423	24x24x6	23 ³ / ₈ x23 ³ / ₈ x5 ¹ / ₂	1000	1500	2000	.21	.26	.30	29
14974	16424	24x12x12	23 ³ / ₈ x11 ³ / ₈ x11 ¹ / ₂	500	750	1000	.21	.26	.29	28
14975	16425	20x20x12	19 ³ / ₈ x19 ³ / ₈ x11 ¹ / ₂	700	1050	1400	.21	.26	.29	39
14976	16426	24x20x12	23 ³ / ₈ x19 ³ / ₈ x11 ¹ / ₂	850	1250	1650	.21	.26	.29	47
14977	16427	24x24x12	23 ³ / ₈ x23 ³ / ₈ x11 ¹ / ₂	1000	1500	2000	.21	.26	.29	58

*Consult factory for additional sizes and performance data

SPECIFICATIONS

Filter Media: Lofted Fiberglass
 Frame: 26 ga Galvanized Steel
 Flammability: UL900 Class 2
 Recommended Final Resistance: 1.5" w.g.
 Maximum Temperature: 180° F

Distributed by:



FLORENCE FILTER CORPORATION

"30 Years of Filter Excellence"

www.florencefilter.com

530 W. Manville • Compton • California 90220
 (310) 637-1137 • FAX (310) 631-4323 • (800) 776-2021