

# F98

## in Disposable Frame

The F98 Superpad has established itself as a premium filter pad. Its application is to stop powdercoating powder, lacquer overspray or general dust. It's primary advantage is a thick but open fiberglass pad at the entry side of the filter with a dense, compressed polyester mat at the exit side. This provides great storage space for heavy duty requirements at the front of the filter and at the same time a straining effect on any fine particles (particularly industrial powders) at the downstream side. For reasons of convenience, some customers prefer this F98 pad to be available as an easy-to-use cartridge. Remove the old cartridge and insert a replacement.

Now this same filter is available in two cartridge frames:

- (1) FFC "A"-type chipboard frames with metal retainers on the entry and exit sides, plus the bonus of a protective weatherproof tape on its perimeter.
- (2) "B"-type chipboard frame with chipboard cross strappings on front and back of filter. "B"-type framing is only available in the 20"x20"x2" size, all others need to be made in the "A"-type frame.

No support grids are needed as both frame models are sturdy enough to be self-supporting.

### Performance Data (20x20x2):

#### Static Pressure:

Initial – @ 350 FPM in inches w.g.	.24
Final – @ 350 FPM in inches w.g.	1.00

#### Efficiencies:

Lacquers	99.9%
Powdercoating Powder	99%
Water-Based Enamels	99%
Chromium Particulates	99%
High-Solids Enamels	99%

Also available: F98 with charcoal in disposable frame.



## FLORENCE FILTER CORPORATION

*"Air Filtration Products since 1971"*

530 W. Manville • Compton • California 90220  
(310) 637-1137 • FAX (310) 631-4323 • (800) 776-2021